



CHADA SALES, INC.

815 E 12th Street • PO Box 3367 • Lawrence, Kansas 66046
Ph: 785-842-1199 • Toll Free: 800-255-6213 • Fx: 785-842-6404
Website: www.chadasales.com • Email: chada@chadasales.com


GRIPPER PLUGS

The Gripper® has become the most popular mechanical plug on the market. And our Gripper plug, like all mechanical plugs is great for long term applications.




The "Original" Gripper® Plug

- Ideal for plumbing system tests
- Made with glass reinforced ABS Plastic
- Extra-large wing nut (easy to install)
- Natural Rubber "O" Ring
- End of Pipe - seals only at the end of a pipe
- Inside of Pipe - seals inside pipe as far as needed



Hub-Fit Gripper® Plug

- Ideal for use in hub fittings
- Great for use in bell-end pipe
- Natural Rubber "O" Ring
- Made with glass reinforced ABS Plastic
- Pressure rated for conducting DWV tests
- Yellow color for greater visibility in pipe





Clean-Out Gripper® Plug

- Patented threaded "O" ring - ensures airtight seal
- Guaranteed to seal any and all damaged threads
- Stainless Steel hardware prevents corrosion
- Made with glass reinforced ABS Plastic
- Natural Rubber "O" Ring
- Black color blends well with cast iron pipe
- NPT sized including hard to find 3/12"

Part #	Nominal Size	Size Usage Range		Maximum Allowable Back Pressure		Product Specifications			
		Minimum Diameter	Maximum Diameter	Air Pressure PSI*	Head Pressure (Feet of Head)	Plug Size Diameter	Plug Size Length	Product Weight	Carton Quantity
Original Gripper® Plugs: End-of-Pipe									
270210	1 1/2" (40 mm)	1.48" (39 mm)	1.65" (42 mm)	17 (1,2 bar)	40 (12 M)	1.46" (38.4 mm)	1.75" (44.5 mm)	.13 lb (.06 kg)	10
270229	2" (50 mm)	1.9" (49 mm)	2.17" (55 mm)	17 (1,2 bar)	40 (12 M)	1.89" (47.8 mm)	1.87" (47.5 mm)	.19 lb (.09 kg)	10
270237	3" (75 mm)	2.8" (71 mm)	3.1" (79 mm)	17 (1,2 bar)	40 (12 M)	2.76" (70.1 mm)	2.5" (63.5 mm)	.375 lb (.17 kg)	10
270245	4" (100 mm)	3.78" (96 mm)	4.06" (103 mm)	17 (1,2 bar)	40 (12 M)	3.76" (95.5 mm)	2.5" (63.5 mm)	.5 lb (.23 kg)	10
270261	6" (150 mm)	5.77" (147 mm)	6.08" (154 mm)	17 (1,2 bar)	40 (12 M)	5.75" (145.9mm)	3.75" (95.3 mm)	2.5 lbs (1.14 kg)	5
270270	8" (200 mm)	7.7" (196 mm)	8.03" (204 mm)	17 (1,2 bar)	40 (12 M)	7.75" (196.7mm)	3.75" (95.3 mm)	3 lbs (41.36kg)	5
Original Gripper® Plugs: Inside-of-Pipe									
270296	4" (100 mm)	3.8" (96 mm)	4.06" (103 mm)	17 (1,2 bar)	40 (12 M)	3.76" (95.5 mm)	2.5" (63.5 mm)	.5 lb (.23 kg)	10
270253	6" (150 mm)	5.77" (147 mm)	6.08" (154 mm)	17 (1,2 bar)	40 (12 M)	5.75" (145.9mm)	3.75" (95.3 mm)	2.5 lbs (1.14 kg)	5
270288	8" (200 mm)	7.7" (196 mm)	8.03" (204 mm)	17 (1,2 bar)	40 (12 M)	7.75" (196.7mm)	3.75" (95.3 mm)	3 lbs (41.36kg)	5
Part #	Nominal Size	Minimum Diameter	Maximum Diameter	Air Pressure PSI*	Head Pressure (Feet of Head)	Plug Size Diameter	Plug Size Length	Product Weight	Carton Quantity
Hub-Fit Gripper® Plugs									
270528	2" (63.5 mm)	2.25" (57.15 mm)	2.45" (62.63 mm)	13 (0,9 bar)	30 (9 M)	2.3" (58.42 mm)	1.9" (48.26 mm)	3.3 oz (.09 kg)	10
270538	3" (88.9 mm)	3.44" (87.38 mm)	3.53" (89.66 mm)	13 (0,9 bar)	30 (9 M)	3.5" (88.9 mm)	2.4" (61 mm)	9.5 oz (.27 kg)	10
270548	4" (114.3 mm)	4.41" (112.01mm)	4.53" (115.06 mm)	13 (0,9 bar)	30 (9 M)	4.4" (111.76 mm)	2.4" (61 mm)	11.9 oz (.34 kg)	10
Clean-Out Gripper® Plugs (with American threads)									
270168	2"	2.16"	2.5"	17	40	2.2"	1.9"	2.4 oz	10
270178	3"	3.23"	3.75"	17	40	3.3"	2.2"	3.5 oz	10
270138	3.5"	3.25"	4.25"	17	40	3.8"	2.2"	7.5 oz	10
270188	4"	4.22"	4.6"	17	40	4.3"	2.2"	9.7 oz	10